

FDX Lightweight Ultra Bovine EID Tag ISO 11784 Compliant



General Description

This generation of Tamperproof EID Tag has a unique design that provides the ultimate in usability, security and retention. This single use tag features a hard plastic Tamperproof cap. Transponder numbers are laser marked in a circular format on the edge of the tag.



Full Duplex Technology (FDX) is utilized with the Bovine EID Tag. FDX is a design principle whereby the return signal initiates as soon as the beginning of the interrogation signal is received and the smoothing capacitor in the transponder has been charged. The return signal is received repetitively and without interruption for as long as a continuous interrogation signal is maintained. A FDX Transponder doesn't have to store energy to be able to return its entire data signal.

Construction

The tag is yellow (1.20" Dia. X .17" Thick) injection molded Polyurethane female with a black plastic Injection molded tamperproof (Tete Rigid) cap. The hard cap of the Lightweight Ultra Bovine tag provides the highest degree of security available, as any attempt to remove the male tag from the female would cause the tag components to break, rendering them unusable.

Application

Allflex FDX Lightweight Ultra Bovine EID tags are applied with the Red Universal Total Tagger Applicator. To apply tags, the Red Blunt Applicator pin must be installed and the Black or White insert must be removed. The New Ultra Retract-O-Matic may also be used to install this tag. Extended small males are used for placement in a deeper location in the ear. See Application Guide.

Ordering Information

SKU	Description
TF-FDX-Y/GESMY-50	FDX Ultra Bovine EID Tag with Yellow Global Extended Small Male 50 Count
TF-FDX-Y/GESMY-100	FDX Ultra Bovine EID Tag with Yellow Global Extended Small Male 100 Count
TF-FDX-Y/GESMY-250	FDX Ultra Bovine EID Tag with Yellow Global Extended Small Male 250 Count

Allflex USA, Inc.

P.O. Box 612266 * Dallas/Fort Worth Airport, TX 75261-2266
800-989-TAGS * Customer Toll Free FAX 877-456-3969

Allflex Canada

3555 Boulevard Choquette * St. Hyacinthe, Quebec J2S 7Z8
866-505-TAGS * FAX 450-261-8028

www.allflexusa.com

FDX Lightweight Ultra Bovine EID Tag ISO Compliant

SPECIFICATIONS

GENERAL	
RFID Compatibility:	ISO 11784 Compliant
Duplex Mode	FDX-B
Operating Frequency	134.2 KHz
Marking	15 Digit Laser Marked Number
Security	Tamper Proof Design
Application Options:	Universal Total Tagger/Ultra Retract-O-Matic
Manufacturers Id Code	982 as per ICAR assigned Manufacturers code
Power:	Passive (inductively powered from transceiver reading equipment)
Agency Certifications:	ISO 11785/ ISO 11784/ ICAR Approved/FCC approved
PHYSICAL/ENVIRONMENTAL	
Dimensions:	1.20" X .17"
Weight:	5.6 Grams
Material:	Polyurethane
Color:	Yellow with black tete rigid cap
Operating Temperature	-0°C-+50°C (
RELIABILITY	
Expected Life:	10 years
PERFORMANCE	
Read Distance:	Up to 75cm (29.53") (Antenna and reading system dependant)

